

#### IP Telephony 1998: PC-Phone




- Allows PCs to connect to any telephone
- Simple extension of PC-PC case
  - Only minor changes to PC software
- Protocols terminated at the gateway
- Two-stage dialing in both directions
  - PC may need a phone number

## IP Telephony 1999: Phone-Phone



- A natural extension of the PC-Phone case
- Gateways are generally outside the PSTN
  - Like ISP modem pools
  - Some tighter integration now required to avoid two-stage dialing
- Gateway-gateway interoperability is critical
- Today's IP telephony networks work this way

# What do IP Telephony Gateways do?



- Call control protocols are translated between PSTN and IP forms
- Circuit-switched streams of digital information representing voice are converted to packets of data representing compressed voice

#### **Low Bit-rate Codecs**

- ITU-T G.723.1 and G.729A are most commonly used on IP networks
  - Early products used non-standard codecs
- 5,300 bit/s (G.723.1) to 8,000 bit/s (G.729A)
  - Possible to carry over dial-up modem lines
  - Many more conversations can be carried on the same circuit
- Model human vocal tract
  - Very poor at reproducing audio that can't be spoken by humans
  - Distort any dual-tone or modulated data signals

#### Other Impairments

- Delay introduced at many points in the path
  - PC audio device drivers and operating system
  - Buffering in transmitter and receiver
    - Receiver buffering required to handle jitter (delay variation)
  - Coding and decoding delay
  - Routers
- Packet loss caused by network congestion
  - · Causes signals to break up
  - Can result in multiple tones (DTMF) or characters
  - Receiver can mask this effect to some extent
- Can be ameliorated by QOS measures
  - Being deployed by some networks now

#### **Text Telephones**

- Small, portable, battery-powered LCD terminals
- Use various modulation schemes depending on country or region
  - All described in ITU-T Recommendation V.18
  - FSK, V.21, V.23, Bell 103, DTMF
    - In North America, most TTs use 5-bit Baudot character set similar to teletypes, on a 45.5-baud FSK modulation which turns on and off for each key
- None are carried well by low-bitrate codecs due to human speech modeling

#### Why not move to Internet Chat?

- Standards already in place and widely used
- Avoids long distance charges
  - All calls to local ISP
- Point-to-point capabilities with instant messaging
  - Be informed when your friends come online
- Multiparty chat capability
- Friends with computers don't need TTs
- Lots of other things you can do with a PC!
- Isn't everybody on the Internet anyway?

#### **Advantages of Text Telephones**

- Compact, lightweight, rugged
  - No hard disk or fragile parts
  - Very long battery life
- Much less complex than computers
  - No setup, no blue screens, no reboots!
  - Easy to connect anywhere (acoustic or modular)
- Don't need a rendezvous server (ILS, ICQ, etc.)
  - Just a point-to-point phone call
  - No modem training time; instant connections
  - Travels well no local ISP access numbers to find

# **Cost of Text Telephone Use**

- Much less expensive than PCs (~\$200)
  - Many TTs provided free to users by charity or agency
- No recurring ISP access charges
  - Local TT calls are "free" (just cost of phone line)
  - No credit card needed to set up an account
- Existing relay services funded by TRS surcharge on local phone bills
  - Funding model won't easily support wholesale upgrades

#### **Users of Text Telephones**

- Many TT users are not computer-literate
  - Disabilities can make training harder
- Some hearing impaired users switch between voice and TT, particularly when using a relay service
  - Can't when using a modem that requires handshaking
- ADA mandates TT access for governments and enterprises
  - Not easy to make changes to laws
- Installed base is huge!
  - People don't like to change if they don't see substantial benefits


#### **How to Move Forward?**

- Chat appliances are coming
  - May be built into telephones
  - Lower cost and complexity
  - But most roadblocks would still exist
- Ubiquitous broadband access will reduce need for low bit-rate codecs
  - · But not nearly soon enough
- IP telephony networks and equipment must support existing text telephone traffic

#### **Potential Solutions**


- Use higher bit-rate codecs
  - G.711 is not economically feasible with current business models
  - Delay, jitter, and packet loss issues would remain
  - G.722.1 could provide "better than toll quality" and also support TTs
- Take text telephone data "out of band"
  - Demodulate at originating gateway, remodulate at destination
  - Well-known technology
    - Already used for DTMF and fax on IP gateways
    - Also used for fax and data modem traffic on international circuits in the PSTN (DCME/PCME)

## **How Can Gateways Support TTs?**



- Gateway must detect TT signals and convert them to packetized data form instead of digitized audio
  - Uses even less bandwidth and is more efficient
- Call control protocols must also be enhanced to indicate the use of TTs

#### **New and Old TTs Can Interwork**



- IP Telephony gateways need TT enhancements
- New IP based TTs or TTs integrated with standalong or PC-based videophones become possible
- "Chat servers" can support multiparty TT calls

# **Steady Progress**

- Standards to be adopted in February
  - Gunnar Hellström will provide an update
- Technology is being developed
  - · Gunnar Hellström will provide a demo, too!
- Industry is committed to deployment
  - It's the right thing to do!
  - The benefits of next-generation networks will be available to all users

# Thank you!

**Questions?** 

#### ATTACHMENT B

#### TEXT TELEPHONY AND TOTAL CONVERSATION IN THE IP REVOLUTION

GUNNAR HELLSTRÖM
Omnitor
Rapporteur in ITU-T SG16
Q9 Accessibility to Multimedia

# Text Telephony and Total Conversation in the IP revolution

Gunnar Hellström,
Omnitor
Rapporteur in ITU-T SG16
Q9 Accessibility to Multimedia

Gunnar.Hellstrom@omnitor.se +46 8 556 002 05 (V.18 + voice + H.320 video +text)


# Accessibility opportunities in IP networks

- IP networks take over telecomm traffic
- Opportunity:
  - Combine text, video and voice
  - Interworking between many ways to access the network
  - Next generation mobile will have IP capabilities
- Important points to consider
  - Interworking with Textphones in the Telephone Network is desired.
  - IP Transit for textphones requires special consideration
  - A simple IP textphone is needed

#### **Total Conversation standards**

- Text conversation need standards as well as video and audio.
- Work is close to completion in ITU-T and IETF to define extension of video telephony to Total Conversation with video, text and voice
- Subsets are possible for text telephony

# Example of a Total Conversation Terminal



# Opportunities with Total Conversation

- Deaf: sign, type or lip-read as the situation calls for.
- Adult deaf: speak and see and get text back.
- Hearing impaired Hear and lip-read as far as possible, revert to text when needed.
- Video relay services: Transfer phone number to call
- Speech impaired: Hear and type. Or hear and speak and revert to typing when needed.
- Anyone: Communicate in preferred mode, type when needed for names, phone numbers etc.

# Opportunities with local additions to Total Conversation

- Screen reader and Braille display makes text conversation accessible to deaf-blind users.
- Voice recognition can make voice conversation convenient with adult deaf users.

# T.140, the common base for text conversation

- Standardised in ITU-T 1998
- Extremely simple end-to-end text chat protocol
- User input to Unicode UTF-8 coded transmission
- UTF-8 transmission to display
- Safe and easy to include everywhere

|--|

## T.140 text protocol

- Character by character transmission
- Character code for any language: ISO 10646 (= Unicode).
- Control from ISO 6429:
  - Erase last character,
  - New line,
  - Select graphic rendition
  - Alert in session
- Transport channel must be specified for each environment.

User application

T.140

Channel

Network